



HOTMELT ROLL COATER Mod. MELTCATOR SU-280

The MELTCATOR is a hot melt roll coater , to apply hotmelts onto materials over 0,5 mm thickness.

The model SU-280 features heavy duty construction and quality workmanship for years of operation.

Our Hotmelt Roll Coater is configured with a Pressure Bar-Attachment for fullsurface or edge gluing shown on picture. For very thick materials the Pressure Bar Attachment can be removed.

The machine can also be ordered without the Pressure-Bar-Attachment .

ACTION : The material will be feed between the pressure roller and the glue application roller. Stripper Fingers picking up the material from the roller.

Standard Features Include:

- Easy, Safe and Simple operation
 - 1 . Turn heater switch on
 2. When correct temperature is reached turn on motor switch.
- Easy adjustment of glue thickness
- Motor Lock-Out unless hot melt is molten
- Variable Speed Motor
- Knurled Roller
- Pressure Bar Attachment

Working size	:	280 mm
Temperature Control	:	up to 190 C°
Warm up time	:	approx. 30 minutes
Motordrive	:	230 volts, 50/60 Hz , other currents/voltages on request.
Power Consumption	:	1700 watt
Machine Dimension	:	58 x 46 x 96 cm
Weight	:	85 kg



SUMBEL GMBH

D-28197 Bremen - Carl-Stockhinger-Str. 5 - Germany
Telf. ++49 (421) 544078 - Fax ++49 (421) 544071
Homepage: <http://www.sumbel.com> - E-Mail: info@sumbel.com