

# Specification

## Boston No. 7 Stitcher

### Capacity

Two sheets to  $\frac{3}{4}$ " (20mm) thick, or more, according to stock. Adjustment by handwheel and gauge.

### Stabbing Attachment

Available as an optional extra, for stabbing up to a maximum of  $1\frac{1}{2}$ " (40mm) thick.

### Table

Height from floor  $31\frac{3}{8}$ " (80cm); width  $5\frac{1}{2}$ " (14cm); length 26" (66cm). Table extension supplied to increase width to  $8\frac{1}{4}$ " (21cm). Fitted with work guides and stops to ensure correct stitch position. Simple change from flat to saddle stitching, by releasing one lock pin.

### Throat

Flat stitching,  $7\frac{3}{4}$ " (20cm) maximum.  
Saddle stitching, 11" (28cm) clearance.

### Wire sizes

Round:  $\cdot 016$ " ( $\cdot 406$ mm) to  $\cdot 022$ " ( $\cdot 558$ mm).  
Flat: to a maximum of  $\cdot 036$ "  $\times$   $\cdot 022$ " ( $\cdot 914$   $\times$   $\cdot 558$ mm).

### Clinchers and Drivers

Interchangeable for flat or round wire.

### Cutters

Two double-ended, reversible cutters, giving four cutting edges.

### Stitch

Crown width,  $\frac{9}{16}$ " (14.3mm).

### Finger Guard

Perspex, allowing clear visibility.

### Tool tray

Fixture on frame; holds spare driver, clinchers and pin-wrench.

### Motor

$\frac{1}{8}$  h.p. motor, 1 or 3 phase AC or  $\frac{1}{8}$  h.p. DC.  
Totally enclosed V-belt drive, with adjustment for tension.

### Speed

150 r.p.m., or 110 r.p.m.

### Floor area

27"  $\times$  26" (68  $\times$  66cm).

### Weight

372lb (168kg), with motor.

